

ZR[®] 120/ZR 200

4-STROKE ENGINE

5-WAY ADJUSTABLE SHOCKS

STR CAT

TRAIL CERTIFIED (ZR 200)

-

ZR° 120 / ZR 200





PASSION STARTS HERE

Start them on a snowmobile that's designed to make them fall in love with riding. Our ZR 120 is perfect for young, first-time riders, while the ZR 200 is trail-certified so your young rider can hit the same trails you do. Let them feel the thrill of the ride, with the right combination of power and control.

KEY FEATURES

ZR 120

- 123cc 4-Stroke Engine
- 5-Way Adjustable Shocks
- Youth-Sized Design
- Painted Chassis
- Standard Handwarmers
- Tether Switch
- Safety Flag

ZR 200

- 192cc 4-Stroke Engine
- Standard Turn Key Electric Start
- 5-Way Adjustable Shocks
- Hand Warmers
- Tether Switch
- Lightweight Slide-Rail Rear Suspension
- Trail Certified

STARTER KIT (ZR 200)

- Tunnel PackTeam Arctic Hand
- Guards
- High Windshield (10-in.)





WARNING: Arctic Cat snowmobiles can be hazardous to operate. Be sure to read and understand your owner's manual and please pay special attention to the safety instructions. All riders should wear a helmet, eye protection, and protective clothing. Riding and alcohol/drugs don't mix. Never attempt maneuvers beyond your capabilities. Arctic Cat recommends that all riders shake a training course. For additional safety and training information, please see your dealer or call 1-800-887-2887. Vehicles shown may include options not included on base model. All materials, specifications, product offerings, accessories, and pricing are subject to change without notice. ADAPT, ALPHA, ALPHA ONE, AMS, ARCTIC CAT, ARCTIC MOUNTAIN SUSPENSION, ARS, ASCENDER, ATAC, AWS, BLAST, C-TEC2, -TEC4, HARDCORE, NORSEMAN, POWER CLAW, PRO CLIMB, RIOT, SLIDE-ACTION, THUNDERCAT, XTRA-ACTION, and ZR are trademarks or registered trademarks of Arctic Cat Inc. All rights reserved. For more information, visit: www.arcticcat.com.

| | ZR 120 | ZR 200 |
|------------------------------|--|--|
| ENGINE | | |
| ENGINE | 120 | 200 |
| ТҮРЕ | 4-stroke | |
| DISPLACEMENT (CC) | 123сс | 192cc |
| COOLING | Air | |
| CYLINDERS | 1 | |
| FUEL CAPACITY (GAL.) | 0.5 | 2.2 |
| OIL SYSTEM CAPACITY (QUART) | 0.6 | |
| POWERTRAIN | | |
| DRIVE CLUTCH | Arctic Centrifugal | Arctic 5.25-in. Diameter (RPM Sensing) |
| DRIVEN CLUTCH | NA | Arctic 6.75-in. Diameter Arctic (Roller Cam) |
| SUSPENSION | | |
| FRONT SUSPENSION | AWS™ | |
| SKI SHOCKS | Hydraulic twin tube | |
| REAR SUSPENSION | Slide-rail, adjustable torsion spring | Slide-rail, adjustable torsion spring, coil-over rear shock |
| FRONT TRACK SHOCK | NA | |
| REAR TRACK SHOCK | NA | Hydraulic twin tube |
| DIMENSIONS | | |
| CHASSIS OVERALL LENGTH (IN.) | 73 | 84 |
| CHASSIS OVERALL WIDTH (IN.) | 35-37 | |
| CHASSIS OVERALL HEIGHT (IN.) | 34 | 36 |
| TRACK TYPE | Cobra | |
| TRACK WIDTH (IN.) | 10 | |
| TRACK LENGTH (IN.) | 67 | 93 |
| LUG (IN.) | 0.75 | 1.00 |
| SKI STANCE (IN.) | 30.5 | 29.5 - 31.5 Adjustable |
| INSTRUMENTATION | | |
| TYPE OF GAUGE | NA | |
| FEATURES | | |
| STARTER | Manual | Electric - key |
| HEADLIGHTS | Halogen 1-bulb | |
| WINDSHIELD | 4-in. low-height | |
| COLOR | Black/Medium Green | |
| STANDARD FEATURES | Hand warmers, safety flag, tether switch | Hand warmers, tether switch |